

## RANGE AND TRAINING REGULATIONS

<p><b>Range:</b> R-210G</p> <p><b>Location:</b> 5408 9586</p> <p><b>Type:</b> Known Distance Automated Field Firing Range</p>	<p><b>Lateral Limits:</b> <b>Left</b> from grid 54280 96029 at 080 degrees mag <b>Right</b> from grid 54247 95903 at 096 degrees mag <b>Boundaries:</b> NA</p>	<p><b>Min/max Engagement Distance:</b> <b>Min</b> 30 meters <b>Max</b> 800 meters</p>	<p><b>Range Facilities:</b> Control Tower, PA system, Firing Line Lighting System, Bleachers, Ammunition Storage Area, Port-a-Johns, 15 Firing Lanes, 168 Stationary Infantry Targets from 75-800 meters, 16 Infantry Moving Targets from 430-700 meters.</p>	
<p><b>Troop Penetration Line:</b> 200 meter line 800 meters for maint.</p>	<p><b>Impact Area:</b> Whiskey</p>	<p><b>Range Phone Number(s):</b></p>	<p><b>Allowable Wpns:</b> Rifle, 5.56 only; Machine gun 5.56 only; M203 (pyro only)</p>	<p><b>Assigned to:</b> CO, MCB</p> <p><b>Date Revised:</b> 060314</p>

### SPECIAL INSTRUCTIONS

1. This range is a COMTS range with thermal target capabilities. All units shall coordinate with the contractor at least 48 hours in advance to arrange for an in-brief and to develop a training scenario. Refer to paragraph 6004 in chapter 6 of this Manual.
2. R210G is a conflict with R210B,C,D,E,F; R212 Tow; and restricts down range movement on R215A when in a "Hot" status.
3. OIC/RSO shall ensure there are no personnel present on the conflicting ranges listed in the special instructions #2 and the creek bed adjacent to the 210 series access road prior to requesting to go into a "hot" status.
4. When R-210G is in a hot status, no personnel on R215A will maneuver down range further than 300 meters (14 foot pole). The RSO from R210G will verify through LONGRIFLE, that the RSO from R215A has been notified of this restriction.
5. R210G may be occupied when R210D,E,F are in a "Hot" status.
6. The firing line on R210G is the only portion of the range that may not be occupied when R210B,C and R212 Tow are in a "Hot" status.
7. This range is approved for static fire from established firing lanes 1-15 only.
8. Cross-lane firing is prohibited. Personnel shall only engage targets assigned to their lane.
9. BZO firing is authorized from the established static firing point for each lane, and within the established range fan limits only.
10. Range Guards shall be posted at grids 53994 95682 (Junction of the 210 series road and the R210G access road) with two way radio communications with the RSO. No personnel or vehicles shall be permitted beyond these points while R210G is in a "Hot" status.
11. All weapons malfunctions shall be corrected per the appropriate TM/FM and unit SOP.
12. All weapons shall be cleared and inspected prior to departing the range.

**SPECIAL INSTRUCTIONS CONTINUED ON NEXT PAGE**

Static Firing Line  
Lanes 1-15 Only  
54280 96029  
to  
54247 95903  
LLL 080 deg mag  
RLLL 096 deg mag

208C



Rng Guard  
53994 95682

R210G 5.56mm

14 Foot Pole

212A

213

214

215A

218A

