

RANGE AND TRAINING REGULATIONS

Range: R-206	Lateral Limits: Left from grid 5517 9259 at 269 degrees mag Right from grid 5518 9260 at 270 degrees mag	Min/max Engagement Distance: Min 5 meters (weapon dependent) Max 25 meters	Range Facilities: Observation tower, bleachers, port-a-johns
Location: 5517 9260	Boundaries: Grids N/A		

Type: BZO/Non-Lethal Familiarization Firing Range

Troop Penetration Line: Not beyond target area	Impact Area: R-206 Impact Area	Range Phone Number(s): None	Allowable Wpns: Machine Guns 7.62mm and below; Rifles, 7.62mm and below; Pistols, .45 cal. and below; Shotguns 12 gauge and below; rubber ball hand grenades	Assigned to: CO, MCB Date Revised: 060502
--	--	------------------------------------	---	---

SPECIAL INSTRUCTIONS

1. Rubber ball hand grenades shall be employed by hand only.
2. 7.62mm is allowed for BZO only – **No EMP.**
3. Helicopters may over fly the area at 1,000' AGL and above. When firing 7.62mm an air sentry shall be designated to observe for aircraft entering into the range surface danger zone. In the event an aircraft enters the range surface danger zone, an immediate cease-fire shall be conducted and LONGRIFLE notified. Firing shall not continue until cleared by LONGRIFLE
4. For all EMP training;
 - RSO will ensure that the top of the head of all targets are no higher than 5 feet;
 - All EMP targets must be of softwood uprights, cardboard backing paper or cardboard targets.
 - Any metal bases used must be soft metal.
5. Any engineer stakes used for pallets must be placed on the outside edges of the pallets.
6. Ensure all weapons are cleared and inspected prior to departing the firing line.
7. All weapon malfunctions shall be corrected per the appropriate TM/FM, and unit SOP.