

RANGE AND TRAINING REGULATIONS

Range: R-300	Lateral Limits: Left from grid 4867 9759 at 120 degrees mag Right from grid 4862 9754 at 126 degrees mag	Min/max Engagement Distance: Min 3 meters (weapon dependent) Max 50 meters	Range Facilities: 3, 7, 10, 15, 25, 30, and 50 yard firing lines; ammo table; port-a-johns
Location: 4864 9756	Boundaries: NA		

Type:
BZO/EMP Range

Troop Penetration Line: Not beyond target area	Impact Area: Range 300	Range Phone Number(s): NA	Allowable Wpns: Rifles, 7.62 and below; pistols, .45 cal. and below; shotguns; machine guns, 7.62 and below	Assigned to: CO, MCB Date Revised: 28 August, 2006
---	-------------------------------	----------------------------------	--	---

GENERAL INSTRUCTIONS

- A safety Brief will conducted prior to each live fire event to all participants.**
- IOT occupy this range unit must have the following personnel/equipment:
 - RSO
 - Corpsman & Safety Vehicle
 - Positive Communication with LONGRIFLE
 - If ammunition is present on range - Ammo Guards will be armed.
- IOT go into a hot status on range unit must have the following personnel/equipment:
 - OIC
 - RSO
 - Corpsman & Safety Vehicle
 - Positive Communication with LONGRIFLE
- RSO will verify the left and right lateral limits utilizing a compass and map.**
 - Overall range lateral limits will be identified.
 - Each firing position lateral limits will be identified.
- The RSO & OIC will personally observe each live fire event.
- A signed ORM must be on hand IOT conduct training.**
- A non-participating Corpsman will be stationed with safety vehicle.**
- A full rehearsal will be conducted prior to live fire.**
- Ammunition will only be issued per event and accounted for on NAVMC 11381.
- After each event, unit leaders will conduct a line out.
- Ensure all weapons are cleared and inspected prior to departing the firing line.
- All weapon malfunctions shall be corrected per the appropriate TM/FM, and unit SOP.

SPECIAL INSTRUCTIONS

- All M249 BZO and 10 meter qualification will be conducted using pallets.
 - Any engineer stakes used for pallets must be placed on the outside edges of the pallets.
- For all EMP training
 - All EMP targets must be of softwood uprights, cardboard backing paper or cardboard targets.
 - Any metal bases used must be soft metal.



300

Range 300